

A successful installation of tierra tiles is highly affected by the installation process. MexicanTiles strongly recommends hiring or consulting a skilled professional tile installer, even for small projects. MexicanTiles is not liable for tile that has been altered from its original state due to improper handling during the installation process. Inspect the tile prior to installation as installation signifies acceptance.

This guide is intended to provide information on frequently asked questions. Opinions vary in the ceramic tile industry about the proper installation of terra cotta tiles.

Installation Recommendations

Note: Always test a small sample tile with the solutions that might be used during installation before applying to an entire area.

- Carefully choose a skilled tile installer.
- Properly lay out material and strategically mix all boxes of tiles prior to installation.
- Make sure the installer is informed of all the procedures and products; and carefully follows the manufacturer's instructions of any solutions such as sealers, grout releases, and cleaners that may be used or come in contact with the tile during the installation process.
- Seal tiles before installation with a penetrating sealer of your choice prior to grouting. We recommend 511 Impregnator Sealer from Miracle Sealants Company for the most porous surfaces such as terra cotta tiles.
- Apply a grout release (like Aqua Mix's) before grouting following the manufacturer's instructions; this process will help protect its inherent textured surface, and reduce grout staining.
- One important consideration as part of the tile selection process is the color of the grout. Depending on the desired final look, there are three basic approaches to selecting the best grout color: matching, contrasting, and neutral. Grout color will affect the product's final appearance.
- Use sanded grout. Premixed epoxy grout is NOT recommended due to its viscosity.
- After the grout has dried completely, clean tiles with Grout Haze Clean-up from Aqua Mix if needed.
- Allow the entire tiled area to dry completely. Depending on environmental climate, it may take up to 24 hours to dry.
- After the installation has been completed, seal grout lines once again with a penetrating sealer.
- If desired and to further protect the tile you may use High Gloss Finish Sealer from Miracle Sealants Company. This surface sealer enhances color while providing resistance to chemicals, stains and dirt.

info@mexicantiles.com 1-619-671-1095



info@mexicantiles.com 1-619-671-1095